CLAIMS

The listing of the claims will replace all prior versions, and listings, of claims in the application:

Listing of Claims:

Claims 1-18 (canceled)

Claim 19 (currently amended): A method of semiconductor wafer processing comprising the steps of:

providing a multi-chamber module including a plurality of vertically-stacked semiconductor wafer process chambers;

providing a loadlock chamber for each of the vertically-stacked semiconductor wafer process chambers, wherein each loadlock chamber having a transfer arm including an upper wafer shelf for carrying unprocessed wafers and a lower wafer shelf for carrying processed wafers, and a semiconductor wafer process chamber;

simultaneously transferring a processed wafer and an unprocessed wafer from <u>one of</u> said process chamber chambers to said respective loadlock chamber.

Claim 20 (currently amended): A method of semiconductor wafer processing according to claim 19 further comprising the step:

evacuating said <u>respective</u> loadlock chamber prior to simultaneously transferring a processed wafer and an unprocessed wafer from <u>one of</u> said process chamber <u>chambers</u> to said respective loadlock chamber.

Claim 21 (currently amended): A method of semiconductor wafer processing according to claim 19, further includes providing a cooling plate below the transfer arm within <u>each of said</u> loadlock ehamber chambers, said method further comprising:

transferring said processed wafer from said lower wafer shelf to said cooling plate.

Claim 22 (currently amended): A method of semiconductor wafer processing according to claim 21 further comprising:

transporting said unprocessed wafer on said upper wafer shelf from said <u>respective</u> loadlock chamber to <u>one of said process chamber chambers</u>;

transferring said unprocessed wafer from said upper wafer shelf to a wafer chuck mounted in one of said semiconductor wafer chamber process chambers,

translating said wafer chuck from a retracted position, past a chemical vapor deposition

injector mounted in <u>one of said semiconductor wafer</u> process chamber <u>chambers</u>, to an extended position, whereby an unprocessed wafer is processed into a processed wafer.

Claim 23 (currently amended): A method of semiconductor wafer processing according to claim 19 further comprising the steps prior to the simultaneously transferring step:

receiving a first unprocessed wafer on the transfer arm;

transferring said first unprocessed wafer to <u>one of said process chamber chambers;</u>
concurrently processing said first unprocessed wafer into a first processed wafer and receiving a second unprocessed wafer on the transfer arm; and

retrieving said first processed wafer by said transfer arm while holding said second unprocessed wafer on said transfer arm.

Claim 24 (currently amended): A method of semiconductor wafer processing comprising the steps of:

providing an atmospheric front end unit including a front end robot for transporting a semiconductor wafer, a multi-chamber module including a plurality of vertically-stacked semiconductor wafer process chambers, a loadlock chamber for each semiconductor wafer process chamber, and a wafer transfer apparatus for each loadlock chamber, each said loadlock chamber and each said wafer transfer apparatus dedicated to a respective wafer process chamber;

transporting a wafer between said atmospheric front end unit and one of said loadlock chambers via said robot; and

simultaneously transferring a processed and an unprocessed wafer from <u>one of said</u> wafer process chamber <u>chambers</u> to said respective loadlock chamber via said wafer transfer apparatus.

Claim 25 (canceled)

Claim 26 (previously presented): The method according to claim 19 wherein the simultaneous transferring is performed by a single-axis wafer transfer arm capable of providing an extended position and a home position.

Claim 27 (previously presented): The method according to claim 24 wherein the simultaneous transferring is performed by a single-axis wafer transfer arm capable of providing an extended position and a home position.